

OS-214 TT



Printing Method	Thermal transfer and direct thermal
Printing Resolution	203 dpi (8dots/mm)
Printing Speed	3 ips (76mm/s)
Printing Length	Max 8" (203mm)
Printing Width	MAX 4.1" (104mm)
Memory	512KB DRAM, 512KB Flash ROM
compact size	W 7.3" x D 10.9" x H 6.0" (W 186 x D 278 x H 153mm)
Ribbon	Wax, Wax/Resin, Resin Standard width 1.3", 2.5", 3.3", 4.3" (33mm, 64mm, 84mm, 109mm) Ribbon roll - OD 1.4"(36mm) with ID 0.5" core (12.5mm) Ribbon length - 3600"(91m)
Communication Interface	Centronics parallel RS-232 serial
Fonts	Int'l character sets standard 5 alpha-numeric fonts from .049"~.23"H (1.25mm~6.0mm) All fonts are expandable up to 24x 24 4 direction 0°~270° rotation Soft fonts are downloadable
Power Source	110/220 VA±10%, 50/60Hz
Barcodes	Code 39, Extended Code 39, Code 93, Code 128 UCC Code 128(Subset A, B, C) Codabar, Interleave 2 of 5, EAN-8 2&5 add on, EAN-13, EAN-128, POSTNET, German POST, Matrix 25, Maxicode, PDF-417, Data Matrix
Graphics	PPLA: PCX, BMP, IMG, HEX, GDI / PPLB: PCX, Binary raster, GDI
Agency Listings	CE, UL, CUL, FCC class A, CCC
Software	ARGOX PPLB Language Windows Driver (Win98/2000/NT/XP) Label editing software – ArgoBar Printer Utility
Media	Media Roll-feed, die-cut, continuous, fan-fold, tag, ticket in thermal paper or plain paper Max width 4.3" (110mm) Min width 1.0" (25mm) Max length 8" (203mm) Min length 0.4" (10mm) Supply roll OD 4.3" (109mm) with ID 1.0" (25mm) core
weight	4.2 lbs (1.9) kg's
Operation Environment	40 F ~ 100 F (4 C~38 C) Humidity : 10~90% non condensing
Optional Items	Cutter, Dispenser kit, Extension Flash memory, Real time clock card, External 8"OD media stacker ArgoKee(Standalone KDU)