

K319 Mobile Printer

- Industrial quality
- 50mm Media roll size
- Adjustable paper width
- Bluetooth 4.0
- Support Windows / Android / iOS



Label printing

Gap detection and black mark detection allow printing of labels in different sizes

Printing features


High printing speed for text in various languages and graphics

Low energy Bluetooth

Supports multiple host connections

Long operating hours

2600mAh battery and highly optimized power management schemes ensure long operating hours without disruptions



Battery



Adapter



Data cable

SPECIFICATION

PRINTER SPECIFICATIONS

| | |
|-----------------------|--|
| Printer Mode | Direct Thermal |
| Maximum Print Width | 3"/72mm |
| Maximum Print Speed | 70mm per second |
| Resolution | 203dpi(8 dots/mm) |
| Print life | 150km(25%Print density or the following)/Each point: 1.5million pulses |
| Power | 19.76Wh(2600mAh)/7.4V Rechargeable lithium polymer battery |
| Character Sets | English, Russian, Arabic, Thai and other languages, and Chinese Japanese Korean characters, graphics, curve, pre-Storage Icon 1D bar-code: UPC-A, UPC-E, CODE39, EAN-13, EAN-8, CODEBAR, CODE128, CODE93, ITF 2D bar-code: QR Code, PDF417, DATAMATRIX |
| Programming Languages | ESC/POS CPCL(Compatibility) |
| Support System | Windows CE/Mobile Support Microsoft Standard SDK、API interface invocation(CE5.0 or above, Mobile5.0 or above) Android Support Google Standard SDK、API interface invocation(2.0 or above) IOS Support IOS System & Supply IOS SDK |

MEDIA SPECIFICATIONS

| | |
|-------------------------|-----------------------------------|
| Media width | 42mm-80mm between any print width |
| Maximum Media Roll Size | 50mm |
| Media Thickness | 1.97~7.09mil |
| Media Type | Labels, Thermal paper |

COMMUNICATION

| | | |
|-----------|------------------------|----------|
| Wired | USB port | USB HOST |
| | Type | Type-C |
| Bluetooth | Bluetooth 2.1+4.0(BLE) | |

PHYSICAL CHARACTERISTICS

| | |
|-------------|------------------|
| Size(L*W*H) | 109mm*107mm*55mm |
| Weight | 354g |

OTHERS

| | |
|-------------------|--|
| Charging interval | ~2.5h |
| Stand-by time | 180-200h |
| Prompt | Paper out prompt, Battery low prompt, Cover/opened prompt, Charging completed prompt, Printing, Communication mode |
| Display | OLED screen |

ENVIRONMENT

Operating Temperature

| | | |
|--------------------------------|----------|--------------|
| Operating Temperature | Min | Max |
| | 32°F(0℃) | +122°F(+50℃) |
| Operating humidity(Relatively) | 20 % | 85 % |

Storage Temperature

| | | |
|----------------------------------|------------|--------------|
| Storage temperature | Min | Max |
| | -4°F(-20℃) | +158°F(+70℃) |
| Storage temperature (Relatively) | 5 % | 95 % |

Urovo Technology Co., Ltd.

For more information, please visit <http://www.urovo.com/en/>

For purchasing or partnership enquiry, please email 400-888-6989

This page is subject to change without prior notice, subject to change without notice