

UROVO

i2000

Smart Minipos Terminal Mini POS, Big Business

The pocket-sized mini body of i2000 contains rich functions and powerful performance. The 4" touch screen is just right, making i2000 exquisite in appearance and compact in structure. All payments are available, magnetic strip, EMV chip & pin, contactless/NFC, QRcode. The system is powered by Android 9.0 and a Qualcomm quad-core high-speed processor, delivering strong performance. A professional scan module is optional to scan bar codes and QR codes efficiently.

Features

LIGHT WEIGHT AND PORTABLE

Mini POS body with 4" touch screen, slim and delicate. Wavy texture on the back makes a good user experience.

HIGH SECURITY

Complete payment certifications (include the latest PCI PTS 6.x), transaction security is fully guaranteed.

ALL IN ONE PAYMENT

Magnetic strip, EMV chip & pin, contactless/ NFC, QR code.

EXCELLENT PERFORMANCE

Powered by Android 9 and Qualcomm quad-core high-speed processor. Besides, a professional scan module is optional.

MULTIPLE CONNECTION

4G/ Wi-Fi/ Bluetooth, Multi methods to make it always connected.



i2000 Android Minipos Terminal

Specifications

O.S. Android 9.0	Processor AP: Quad-core 1.3GHz SP: MH 1901H	Memory RAM:1GB ROM:8GB RAM:2GB ROM:16GB (optional)
Display 4.0" display, 480×800	Button PWR button, Vol+/- button, Custom button	Network Connection FDD-LTE, TDD-LTE, WCDMA, CDMA2000, CDMA, GSM Bluetooth: BT 4.1+BR/EDR+BLE Wi-Fi:802.11 b/g/n 2.4GHz
Camera Rear 0.3MP FF (2MP FF optional)	Scanning Rear camera decoding 2D scan engine (optional)	Payment Magnetic stripe IC Card Contactless Card
Audio Speaker 1W (optional), Buzzer	Positioning GPS, A-GPS, BEIDOU, GLONASS	Slot 1xNano SIM+1xSAM 1xNano SIM+1xSAM+1xSAM/SIM(optional) Micro SD/TFx1, up to 128 GB(optional)
Interface 1xType-C (data transferring and charging, USB OTG 2.0) Pogopin 2pin (optional)	Notification LED Contactless Notification LED, Blue/ Yellow/ Green/ Red Power LED	Battery 3.8V/ 2500mAh, Polymer Lithium Battery
Adaptor Input: 100~240V AC 50~60Hz Output: 5V/1A	Environment Operating: -10°C~50°C (14°F~122°F) Storage: -20°C~70°C (-4°F~158°F) Humidity: 5%RH~95%RH (No condensation)	Physical L x W x H (mm): 133.5 x 70 x 17 Weight (g): 222g
Certification PCI PTS 6.x, EMV L1&L2, Master- Card TQM, EMV Contactless L1, MasterCard Contactless, Visa PayWave, CE		